



FG4300

ADJUSTABLE IN-GROUND WELL LIGHT




* Corrosion Resistant-Ocean Front Placement

DABMAR
LIGHTING

DABMAR LIGHTING INCORPORATED

320 Graves Ave . Oxnard, CA 93030 . 805.604.9090 . f: 805.604.9050 . www.dabmar.com
4693 19th Street Ct E . Bradenton, FL 34203



FG4300-LED40-S

FG4300-LED40-RGBW

2 (two) - 3/4" Knockouts on bottom of housing

- FG4300 - 15.60 lbs
- FG4310 - 22 lbs
- FG4310-MT - 25 lbs
- FG4320 - 22 lbs
- FG4320-MT - 25 lbs
- FG4330 - 22 lbs
- FG4330-MT - 25 lbs
- FG4380 - 22 lbs
- FG4380-MED - 22 lbs
- FG4380-MED/MT - 24 lbs
- FG4380-MT - 24 lbs
- FG4385 - 24 lbs
- FG4385-MED - 24 lbs
- FG4385-MED/MT - 25 lbs
- FG4385-MT - 25 lbs
- FG4390 - 25 lbs
- FG4390-MED - 25 lbs
- FG4390-MED/MT - 25 lbs
- FG4390-MT - 25 lbs
- FG4395-MED - 26 lbs
- FG4395-MED/MT - 26 lbs

Overall Dimensions:
14.00"H x 12.19"W x 12.19"D

Weight: SEE ABOVE
Box Dimensions:
14.31"H x 12.63"W x 12.50"D

Lamp Included
Lamp Not Included (FG4300)

- ▶ **Material:** Fiberglass
- ▶ **Lens:** Clear, Heat Resistant, Tempered Glass

MODEL NUMBER	LAMP TYPE	ILLUMINANT TYPE	WATTS (W)	VOLTS (V)	LAMP(S) INCLUDED?
FG4300	PAR38	INCANDESCENT	150	120	NO
FG4300-LED18-F	PAR38-LED	LED FLOOD	18	120-277	YES
FG4300-LED18-S	PAR38-LED	LED SPOT	18	120-277	YES
FG4300-LED40-S	PAR56-LED	SMD LED SPOT	40	100-265	YES
FG4300-LED40-RGBW	PAR56-LED	SMD LED SPOT	40	100-265	YES
FG4310	HID	HPS	70	120	YES
FG4310-MT	HID	HPS	70	MT	YES
FG4320	HID	HPS	100	120	YES
FG4320-MT	HID	HPS	100	MT	YES
FG4330	HID	HPS	150	120	YES
FG4330-MT	HID	HPS	150	MT	YES
FG4380	HID	MH/DE	70	120	YES
FG4380-MED	HID	MH	70	120	YES
FG4380-MED/MT	HID	MH	70	MT	YES
FG4380-MT	HID	MH/DE	70	MT	YES
FG4385	HID	MH/DE	100	120	YES
FG4385-MED	HID	MH	100	120	YES
FG4385-MED/MT	HID	MH	100	MT	YES
FG4385-MT	HID	MH/DE	100	MT	YES
FG4390	HID	MH/DE	150	120	YES
FG4390-MED	HID	MH	150	120	YES
FG4390-MED/MT	HID	MH	150	MT	YES
FG4390-MT	HID	MH/DE	150	MT	YES
FG4395-MED	HID	MH	175	120	YES
FG4395-MED/MT	HID	MH	175	MT	YES

- ▶ **Installation Type:** Rated for In-Ground Soil and Concrete Applications
- ▶ **Available Finish:** Bronze
- ▶ **PAR56 Beam Angle:** 15°
- ▶ **Remote Included with PAR56 RGBW**
- ▶ **ETL Approved**

LED Available in Warm or Cool White



DABMAR LIGHTING INCORPORATED

320 Graves Ave . Oxnard, CA 93030 . 805.604.9090 . f: 805.604.9050 . www.dabmar.com

4693 19th Street Ct E . Bradenton, FL 34203