

## FF109-300 1 Hour Fire Rated Light Cover

### Step 1

- Hanger bars of the light fixture shall be screwed to the joists in addition to the tabs being hammered into the joists, following the light manufacturer's installation instruction.



### Step 2

- Place Tenmat FF109 cover over the fixture.
- Slit the cover to fit over the hanger bars of the fixture.
- Cut four slits with a size up to 1" max.



### Step 3

- The wire can be fed through one of the cover vent holes located at the top.
- Follow the light manufacturer instructions to make proper connections.



### Step 4

- Put the cover on top of the fixture. Check for secure fit, and make sure the cover overhangs the hanger bars.
- The FF 109 Light Cover must fit flush with the back surface of the drywall board.



Ensure the cover fits your chosen light fixture.

*FF109-300 Overall Dimensions:*

- Inside Diameter 12 3/8"
- Inside Height 7 3/8"



**WARNING:** BE SURE THE ELECTRICITY TO THE SYSTEM YOU ARE WORKING ON IS TURNED OFF; EITHER THE FUSE REMOVED OR THE CIRCUIT BREAKER SET AT OFF.

**CONTAINS STONE WOOL INSULATION**

Stone fibers may cause temporary mechanical irritation to the skin, throat, nose and eyes.

**FIRST AID**

**Skin**

If irritation occurs, do not rub or scratch. Rinse under running water prior to washing with mild soap and water. Consult a physician if irritation persists.

**Throat and Eyes**

If irritation occurs, flush eyes with water and/or drink water to clear throat. Do not rub the eyes. Consult a physician if irritation persists.

**PRECAUTIONS**

- Wear long sleeve, loose fitting clothing, gloves and eye protection.
- For additional information, refer to the Material Safety Data Sheet (MSDS).