

Reed

Picture Light 3000K

Fixture Type:
Catalog Number:
Project:
Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PL-11017 17"	3000K	BK Black BN Brushed Nickel	18W	569	380

Example: PL-11017-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

The perfect complement to any display piece. Conserves fine art while providing superior color rendering.

FEATURES

- Light source rotates 150 degrees
- Simple, elegant slim profile design
- Conversion plate for 4" | box included.
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- Driver concealed within the canopy
- 5 Year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120-277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10%, 0-10V: 100-10%, TRIAC: 100-10%


Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed


Construction: Aluminum hardware with acrylic diffuser



FINISHES:



LINE DRAWING:



WAC LIGHTING

Reed

Picture Light 3000K

Fixture Type:
Catalog Number:
Project:
Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PL-11025 25"	3000K	BK Black BN Brushed Nickel	21W	825	544

Example: PL-11025-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

The perfect complement to any display piece. Conserves fine art while providing superior color rendering.

FEATURES

- Light source rotates 150 degrees
- Simple, elegant slim profile design
- Conversion plate for 4" J box included.
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- Driver concealed within the canopy
- 5 Year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120-277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10%, 0-10V: 100-10%, TRIAC: 100-10%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed


Construction: Aluminum hardware with acrylic diffuser



FINISHES:



LINE DRAWING:



WAC LIGHTING

Reed

Picture Light 3000K

Fixture Type:
Catalog Number:
Project:
Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PL-11033 33"	3000K	BK Black BN Brushed Nickel	28W	1072	747

Example: PL-11033-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

The perfect complement to any display piece. Conserves fine art while providing superior color rendering.

FEATURES

- Light source rotates 150 degrees
- Simple, elegant slim profile design
- Conversion plate for 4" J box included.
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- Driver concealed within the canopy
- 5 Year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120-277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10%, 0-10V: 100-10%, TRIAC: 100-10%


Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed


Construction: Aluminum hardware with acrylic diffuser



FINISHES:



LINE DRAWING:



WAC LIGHTING

Reed

Picture Light 3000K

Fixture Type:
Catalog Number:
Project:
Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PL-11042 42"	3000K	BK Black BN Brushed Nickel	30W	1618	1000

Example: PL-11042-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

The perfect complement to any display piece. Conserves fine art while providing superior color rendering.

FEATURES

- Light source rotates 150 degrees
- Simple, elegant slim profile design
- Driver conceals within the canopy
- Conversion plate for 4" | box included.
- Trimless spackle cover available for 4" square junction box recessed in drywall thicknesses of 1/2", 5/8", 1", and 1-1/4"; accessory not included and can be ordered separately (model# CP-TL-WT)
- Driver concealed within the canopy
- 5 Year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120-277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10%, 0-10V: 100-10%, TRIAC: 100-10%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed

Construction: Aluminum hardware with acrylic diffuser




FINISHES:



Nickel

LINE DRAWING:



PL-11042